



Thinkpower TP Series Three Phase Solar GTI

17.0KW/20.0KW/25.0KW



Big LCD display



Power export limit



Compact and easy to install



Wifi/GPRS/Lan communication optional

Thinkpower Romania: Bucuresti,sector2,str.Delea Veche nr24,CorpA,etaj6,modul M1



Simpler

Quick and easy single person installation
Fault codes warning view on LCD display
smart meter optional



Safer

comply with international quality standards
tested by TUV,BV,Dekra etc.



Great reliability

IP65 ingress protection
10+years R&D accumulation and support

ANYTIME, ANYWHERE

REMOTE MONITORING PLATFORM

Monitor system performance in
real-time via smartphone app or
web portal using our advanced
monitoring platform .



TP Series Three Phase



For more about Thinkpower TP series grid tie inverter
please visit www.pvthink.com

THREE PHASE SOLAR GRID TIED INVERTER

Technology Data

Model No	TP17KTL	TP20KTL	TP25KTL
Input (DC)			
Max DC power (W)	25500	30000	30000
Max DC voltage (Vdc)	1000	1000	1000
Min working voltage (Vdc)	250	250	250
MPPT voltage range (Vdc)	250~850	250~850	250~850
Max input current / per string (A)	26/26	26/26	26/26
Number of MPP trackers	2	2	2
Number of input string	4	4	4
Output (AC)			
AC nominal power (W)	17000	20000	25000
Max AC apparent power (VA)	18700	22000	27500
Max output current (A)	25	30	36
Nominal AC output		50/60 Hz; 400 Vac	
AC output range		45/55 Hz ; 280 ~ 490 Vac (Adj)	
Power factor		0.8leading...0.8lagging	
Harmonics		< 1.5%	
Grid type		3 W/N/PE	
Efficiency			
Max efficiency	98.5%	98.6%	98.7%
Euro efficiency	98.1%	98.1%	98.2%
MPPT efficiency	99.9%	99.9%	99.9%
Safety and Protection			
DC reverse-polarity protection		yes	
DC breaker		yes	
DC/AC SPD		yes	
Leakage current protection		yes	
Insulation Impedance Detection		yes	
Residual Current protection		yes	
General Parameters			
Dimension (W/H/D)(mm)		510/484/272	
Weight (kg)		35	
Operating temperature range (°C)		-25 ~ +60	
Degree of protection		IP65	
Cooling concept		Natural convection	
Topology		Transformerless	
Display		LCD	
Humidity		0-95%, no condensation	
Communication		Standard WIFI; RS485 (optional)	
Warranty		5 years; 5/7/10 years for optional	
Certificates and Approvals			
CQC, VDE-AR-N4105, VDE0126-1-1, AS4777, IEC61727, IEC62116			